

JCB 505-20TC TELEHANDLER

PRODUCTIVITY AND PERFORMANCE



STANDARD FEATURES

- 5,500 lb lift capacity with boom retracted; 3,900 lb lift capacity at full height
- Skid steer coupler option, manual or hydraulic, for added versatility in attachment use
- 74 hp JCB by Kohler engine with no aftertreatment requirements
- One of the largest cabs in the industry for the most comfortable working area
- Low pivot point and no external boom hoses for superior visibility
- LiveLink telematics standard



LIFT CAPACITY OF 1,750 LB AT 11.5 FT OF FORWARD REACH



505-20 TOOL CARRIER



f/JCBNA @JCBNA JCBNA www.jcb.com

STATIC DIMENSIONS


Overall height*	ft-in (m)	6-2 (1.89)
Overall width (over tires)*	ft-in (m)	6-0 (1.84)
Inside width of cab	ft-in (m)	2-11 (0.88)
Front track	ft-in (m)	5-0 (1.53)
Wheelbase	ft-in (m)	7-10 (2.39)
Overall Length to front tires	ft-in (m)	11-1 (3.38)
Overall length to front carriage	ft-in (m)	13-1 (4)
Ground clearance	ft-in (m)	0-9 (0.23)
Front wheel center to carriage	ft-in (m)	3-4 (1.02)
Rear wheel center to rear face	ft-in (m)	2-0 (0.6)
Outside turn radius (over tires)	ft-in (m)	12-1 (3.7)
Carriage roll back angle	degrees	11
Carriage dump angle	degrees	114
Weight	lb (kg)	12,100 (5,490)
Tires	industrial	12 x 16.5

*Dependent upon tire specified

LIFT PERFORMANCE

Maximum lift capacity	lb (kg)	5,500 (2,500)
Lift capacity to full height	lb (kg)	3,900 (1,750)
Lift capacity at full reach	lb (kg)	1,750 (800)
Lift height	ft-in (m)	20-0 (6)
Reach at maximum lift height	in (m)	-6 (-0.15)
Maximum forward reach (to front of carriage)	ft-in (m)	11-6 (3.5)

Complies with stability test ANSI B56.6



THE JCB CONSTRUCTION RANGE

COMPACT EXCAVATORS



TELESCOPIC HANDLERS -LIFT & PLACE



TELESCOPIC HANDLERS -TOOL CARRIER



WHEELED EXCAVATORS



TRACKED EXCAVATORS



ELECTRIC SCISSORS



ROUGH TERRAIN FORKLIFTS



TELETRUKS



WHEEL LOADERS



TELESKIDS



SKID STEER AND COMPACT TRACK LOADERS



BACKHOE LOADERS

